


acpo *ltd.* product data 505 T

Product: 505 T THERMAL TRANSFER POLYPROPYLENE FILM

Description: 505 T is a thermal transfer printable clear polypropylene film. Based on a tough biaxially-oriented polypropylene film, with high strength in the machine and cross directions, coated with a high grade, water clear emulsion acrylic system. 505 T offers excellent acid, chemical and oil resistance. *“Testing should be done on your specific printer.”*

**Nominal:
Values**

Construction:



Backing/Face	1.0	Biaxially-Oriented Polypropylene film (BOPP)
Adhesive	.3	5 lbs./Ream Emulsion Acrylic
Total Thickness (mils)	1.3	+/- 10% tolerance

Performance:

Peel Adhesion to steel (oz/in of width) (180 degree peel @ 12 in/min)	13	30 min. conditioning
	18	24 hr. conditioning
Un-wind Adhesion (oz/in of width) (180 degree peel @ 12 in/min)	12	30 min. conditioning
Adhesive Tensile Strength (oz/in of width) (Loop tack)	13	
Film Elongation (% at break)	160	MD
	60	TD
Temperature Range (degrees F)		
Application	+32 to +150	
Operating	0 to +180	

Roll Tolerances:

Roll Length	+/- 5% of roll length	
Roll Width	+/- .0625 (1/16th)	
Appearance: (particulate contamination) (parts / msi)	0 to 5	>100 micron
	5 to 15	< 50 micron
	10 to 25	< 10 micron

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants and guarantees for accuracy and completeness. Because of the variety of possible uses, THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER SHOULD TEST THE SUITABILITY FOR EACH INTENDED USE BEFORE USING. This product may not be suitable for use on metallic or dark reverse printed labels. **acpo ltd** WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF PRODUCTS OR FOR THE INCIDENTAL OR CONSEQUENTIAL DAMAGES. **acpo ltd** warrants the product(s) to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of the initial date of shipment, **acpo ltd** shall, upon notification thereof and substantiation that the products have been stored and applied within **acpo's** ltd standards, correct such defects by suitable repair or replacement without charge at **acpo's** ltd plant or at the location of the products (at **acpo's** ltd election); provided, however, if **acpo ltd** determines that repair or replacement is not commercially practical, **acpo ltd** shall issue a credit in favor of the BUYER in an amount not to exceed the initial purchase price of the product from **acpo ltd**.